

## PHBN170005 Series

---



### Product Features

---

- With the excellent heat management, the lamp and-sensitive electronic componnets, e.g control gear and led's can work to their full potential throughout their entire life
- Equipped with PHILIPS light source, CRI > 80/90, has high luminous efficiency, stable performance and high consistency of light and color
- Serialized products, classic design, fit for different applications
- Provide interface for smart scheme or emergency solution

### Main application

---

- Shop window
- Accent lighting
- Goods shelf
- Merchandise display

## Technical specifications


Prouduct item	PHBN170005-1	/-2	/-3	/-4
Installation	Track, Surface mounted optional			
Housing color	Black White Titanium			
Power supply	220-240VAC/50-60Hz			
Watt(W)	10	15	25	35
Lumen LED(lm)	1000	1500	2500	3500
System efficacy(lm/w)	>70			
CCT	2700K,3000K,3500k,4000K,5000K			
CRI	80, 90			
SDCM	<= 3 step			
Beam angle(°)	15, 24, 36			
Tilting	90°			
Turning	355°			
Size(mm)	φ50x160mm	φ60x180mm	φ71x185mm	φ83x200mm
Lifetime	30,000 hrs			
Protection class	IP20			
Material	Aluminum			



## Accessories



Tensile control



Honeycomb louvre